

Usage: qpdf [options] infilename outfilename

An option summary appears below. Please see the documentation for details.

Basic Options

```
--password=password          specify a password for accessing encrypted files  
--linearize                 generate a linearized (web optimized) file  
--encrypt options --         generate an encrypted file  
--decrypt                   remove any encryption on the file
```

If neither `--encrypt` or `--decrypt` are given, qpdf will preserve any encryption data associated with a file.

Encryption Options

```
--encrypt user-password owner-password key-length flags --
```

Note that `--` terminates parsing of encryption flags.

Either or both of the user password and the owner password may be empty strings.

key-length may be 40 or 128

Additional flags are dependent upon key length.

If 40:

```
--print=[yn]                  allow printing  
--modify=[yn]                 allow document modification  
--extract=[yn]                allow text/graphic extraction  
--annotate=[yn]               allow comments and form fill-in and signing
```

If 128:

```
--accessibility=[yn]          allow accessibility to visually impaired  
--extract=[yn]                 allow other text/graphic extraction  
--print=print-opt              control printing access  
--modify=modify-opt            control modify access  
--cleartext-metadata          prevents encryption of metadata  
--use-aes=[yn]                 indicates whether to use AES encryption  
--force-V4                     forces use of V=4 encryption handler
```

print-opt may be:

```
full                         allow full printing  
low                          allow only low-resolution printing  
none                         disallow printing
```

modify-opt may be:

```
all                          allow full document modification  
annotate                     allow comment authoring and form operations  
form                        allow form field fill-in and signing  
assembly                    allow document assembly only  
none                        allow no modifications
```

The default for each permission option is to be fully permissive.

Specifying `cleartext-metadata` forces the PDF version to at least 1.5. Specifying use of AES forces the PDF version to at least 1.6. These options are both off by default.

The `--force-V4` flag forces the V=4 encryption handler introduced in PDF 1.5 to be used even if not otherwise needed. This option is primarily useful for testing qpdf and has no other practical use.